

Technical specs

Type of fuel	Wood
Recommended surface	1050 to 1900 sq. ft.
Blower	130 CFM
Maximum output - EPA test wood	38700 BTU
Maximum output - seasoned cord wood	75000 BTU
Color	Metallic black
Minimum fireplace opening	29"W x 17"D x 24"H
Exterior dimensions	27"W x 26.5"D x 22"H
Exhaust pipe diameter	6"
Type of chimney	2,100 deg. F (1150 deg. C)
Recommended chimney diameter	6"
Minimum chimney height	12'
Firebox dimensions	21.25"W x 16.75"D
Log positioning	Width
Maximum log length	20"
Door opening dimensions	17.75"W x 9"H
Type of door	Glass with cast iron frame
Minimum clearances to combustibles (Data expressed in inches. 1 inch = 25.4 mm)	
Combustible side wall to unit	13"
Combustible side mantle to unit	10"
Combustible top mantle to unit	22"
Combustible shelf to unit	29"
Minimum floor protection in front of unit	18" / 16"
Projection in the room minimum / maximum	8.75" x 10.75"
Glass surface	16.25"L x 9.5"H
Steel thickness	5/16"
Weight	380 lbs
Warranty	Limited lifetime
Test standard - safety	ULC-628 , UL 1482
Test standard - emissions	E.P.A. Methode 28