

Technical specs

Type of fuel	Wood			
Recommended surface	1050 to 1900 sq. ft.			
Maximum output - EPA test wood	38700 BTU			
Maximum output - seasoned cord wood	75000 BTU			
Color	Metallic black			
Exterior dimensions	25½"W x 25¾"D x 30¾"H			
Exhaust pipe diameter	6"			
Type of chimney	2,100 deg. F (1150 deg. C)			
Recommended chimney diameter	6"			
Minimum chimney height	12' (3,66 m)			
Firebox dimensions	21¼"W x 16¾"D			
Log positioning	Width			
Maximum log length	20"			
Door opening dimensions	17¾"W x 9"H			
Type of door	Glass with cast iron frame			
Minimum clearances to combustibles (Data expressed in inches. 1 inch = 25.4 mm)				
	Canada		USA	
	Single walled pipe	Double walled pipe	Single walled pipe	Double walled pipe
Back	14"	6"	14"	
Sides	12"	12"	12"	12"
Corners	7"	5"	7"	5"
Top*	84"	84"	84"	84"
* Measured from floor.				
Glass surface	16¼"W x 9½"H			
Steel thickness	5/16"			
Weight	395 lbs (180 kg)			
Warranty	Limited lifetime			
Test standard - safety	ULC S-627, UL 1482			
Test standard - emissions	EPA Method 28			